



YSFTA Uses the same locking method as YSFT locknut, but this nut has wrench holes on the radius side and back surface side, making it easy for different assembly environment requirements.

- Material Composition: SCM440(42CrMo4)
- Hardness: HRC28°~32°
- Thread Accuracy: ISO 4H
- Manufacturing Method: High Precision Grinding
- Run Out: 0.002mm
- Thread Accuracy: ISO 4H
- Manufacturing Method: High Precision Turning
- Run Out: 0.005mm

YSFTA

Thread	D	h	d	d1	c	c1	n-Øb	n-Øb1	n-m	MAX. Nm
YSFTA-M25 x 1.5P	42	20	35	26	32.5	11	6-Ø4.3	6-Ø4	3-M6	8
YSFTA-M30 x 1.5P	48	20	40	32	40.5	11	6-Ø4.3	6-Ø5	3-M6	8
YSFTA-M35 x 1.5P	53	20	47	38	45.5	11	6-Ø4.3	6-Ø5	3-M6	8
YSFTA-M40 x 1.5P	58	22	52	42	50.5	12	6-Ø4.3	6-Ø5	3-M6	8
YSFTA-M45 x 1.5P	68	22	58	48	58	12	6-Ø4.3	6-Ø6	3-M6	8
YSFTA-M50 x 1.5P	70	24	63	52	61.5	13	6-Ø4.3	6-Ø6	3-M6	8
YSFTA-M55 x 1.5P	75	24	70	58	66.5	13	6-Ø4.3	6-Ø6	3-M6	8
YSFTA-M60 x 1.5P	84	24	75	62	74.5	13	6-Ø5.3	6-Ø6	3-M8	18
YSFTA-M65 x 1.5P	88	25	80	68	78.5	13	6-Ø5.3	6-Ø6	3-M8	18
YSFTA-M70 x 1.5P	95	26	86	72	85	14	6-Ø5.3	6-Ø8	3-M8	18
YSFTA-M75 x 1.5P	100	26	91	77	88	13	6-Ø6.4	6-Ø8	3-M8	18
YSFTA-M80 x 2.0P	110	30	97	83	95	16	6-Ø6.4	6-Ø8	3-M8	18
YSFTA-M85 x 2.0P	115	32	102	88	100	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M90 x 2.0P	120	32	110	93	108	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M95 x 2.0P	125	32	114	98	113	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M100 x 2.0P	130	32	120	103	118	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M110 x 2.0P	140	32	132	112	128	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M120 x 2.0P	155	32	142	122	140	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M130 x 3.0P	165	32	156	132	153	17	6-Ø6.4	6-Ø8	3-M10	35
YSFTA-M140 x 3.0P	180	32	166	142	165	17	6-Ø6.4	6-Ø10	3-M10	35
YSFTA-M150 x 3.0P	190	32	180	152	175	17	6-Ø6.4	6-Ø10	3-M10	35
YSFTA-M160 x 3.0P	205	32	190	162	185	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M170 x 3.0P	215	32	205	172	195	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M180 x 3.0P	230	32	215	182	210	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M190 x 3.0P	240	32	225	192	224	17	6-Ø8.4	6-Ø10	3-M10	35
YSFTA-M200 x 3.0P	245	32	237	202	229	17	6-Ø8.4	6-Ø10	3-M10	35