



※ Screws included with this model.

YSMSW locknut uses steel's elasticity characteristics to securely fix the locking nut in the axial direction. This type of nut is thicker and the outer diameter is larger, making this nut suitable for heavier axial loads.

- Material Composition: SCM440(42CrMo4)
- Hardness: HRC28°~32°
- Thread Accuracy: ISO 4H
- Manufacturing Method: High Precision Turning
- Run Out: 0.005mm



YSMSW

Thread	D	h	h1	g	t	d	n-m	MAX. Nm
YSMSW 20/28-M20 x 1.5P	42	28	11	6	2.5	38	4-M4	3.5
YSMSW 20/40-M20 x 1.5P	52	40	11	7	3	42	4-M4	3.5
YSMSW 25/28-M25 x 1.5P	47	28	11	7	3	43	4-M4	3.5
YSMSW 25/40-M25 x 1.5P	62	40	11	8	3.5	47	4-M4	3.5
YSMSW 30/28-M30 x 1.5P	52	28	11	7	3	48	4-M4	3.5
YSMSW 30/44-M30 x 1.5P	68	44	11	8	3.5	52	4-M4	3.5
YSMSW 35/28-M35 x 1.5P	60	28	11	8	3.5	53	4-M4	3.5
YSMSW 35/44-M35 x 1.5P	73	44	11	8	3.5	60	4-M4	3.5
YSMSW 40/28-M40 x 1.5P	65	28	11	8	3.5	58	6-M4	3.5
YSMSW 40/44-M40 x 1.5P	75	44	11	8	3.5	62	6-M4	3.5
YSMSW 45/28-M45 x 1.5P	70	28	11	8	3.5	63	6-M4	3.5
YSMSW 45/44-M45 x 1.5P	90	44	11	10	4	70	6-M4	3.5
YSMSW 50/32-M50 x 1.5P	75	32	11	8	3.5	68	6-M4	3.5
YSMSW 50/46-M50 x 1.5P	95	46	11	10	4	75	6-M4	3.5
YSMSW 55/46-M55 x 1.5P	100	46	12	10	4	80	6-M5	4.5
YSMSW 60/46-M60 x 1.5P	100	46	12	10	4	85	6-M5	4.5
YSMSW 65/46-M65 x 1.5P	110	46	12	10	4	90	6-M5	4.5
YSMSW 70/46-M70 x 1.5P	115	46	12	10	4	95	6-M5	4.5